



180mm, Spindle Thread M14 X 2, 2400W, 8,500rpm, 5.9Kg

180mm 2 Speed Sanding &

polishing, Spindle Thread

M14 x 2, 750W, 1,900rpm/

3,400rpm, 2.9Kg





180mm, Spindle Thread M14 x 2, 2,600W, 8,500rpm, 5.1Kg

180mm, Spindle Thread

M14 x 2. Electronic control.

1,250W, 0-3,400rpm, 2,8Kg

SP 18VA



230mm, Spindle Thread M14 x 2, 2,000W, 6,600rpm, 4.3Kg



G 23SW2 230 mm, Spindle Thread M14 x 2, 230mm, Spindle Thread M14 x 2, 2,000W, 6,600rpm, 5.1Kg 2,200W, 6,600rpm, 5.1Kg

SV 12SG

114mm with dust bag Pad size

14,000rpm, Orbit 28,000rpm, 1,1Kg

110X100mm, 200W. Spindle



SV 13YA

Variable speed Sanding

paper & pad size 125mm,

Orbital dia 3.2mm, 230W,

7,000-12,000rpm, 1.4Kg

230mm, Spindle Thread M14 x 2, 2,400W, 6,600rpm, 6.1 Kg



Precise grinding, Max Collet chuck 6mm, 520W, 29,000rpm, 1.7Kg

Sanding paper & pad size

230W, 12,000rpm 1.4Kg

125mm, Orbital dia 3,2mm.

SV 13YB 🥞



S 15SB Vertical type



150mm, Spindle Thread M16 x 2, 705W, 4,500rpm, 2.0Kg

SB 8V2 🐬 Variable speed Belt size 76X533mm, 1,020W, No load speed 250-450rpm, 4.3Kg

C 7SS

Blade dia 190mm, Max cut. Depth 68mm @ 90° & 46mm @ 45°, 1,050W, 5,500rpm, 3.4Kg

C 7ST

Blade dia 185mm, Max cut.

Depth 60mm @ 90° & 47mm @ 45°, 1,710W, 5,800rpm, 4.6Kg

235mm, Max cut. Depth 86mm @ 90° & 65mm @ 45°, 2,000W, 5,200rpm, 7.0Kg

With dust bag Pad size 92X184mm,

M 6ST

Constant speed

Collet chuck 6.35mm,

505W, 32000rpm, 1.5Kg

Cutting cap. In Steel 1.6mm

Stainless 1.2mm,

- **4**

400W, 2,300rpm, 1.6Kg

UM 16VST2

1600W, 5.6Kg

Max Stirrer Diameter-160mm,

300-650rpm/150-300rpm,

CN 16SA

180W, Spindle 10,000rpm,

Orbit 20,000rpm, 1,3Kg

FSV 10SA

C 8FSHE Blade dia 216mm, Compound Miter 45° & Bevel 45° - 45 x 220mm, 1,050W, 5,500rpm, 14.5Kg





C 12LCH Blade dia 305mm, Compound Miter 45° & Bevel 45° - 40 x 140mm, 1,520W, 4,000rpm, 19.5Kg



Variable speed Wood 65mm Steel plate 6mm, 400W,

Base Tilt angle 45° Right / Left, 0-3,000rpm, 1.5Kg

CJ 90VST

Variable speed Wood 90mm, Steel plate 8mm, Base Tilt angle 45° Right / Left, 705W, 850-3,000rpm, 2.2Kg

CJ 160V a 160mm, 800W, Length of Stroke 26mm,

800-2,800rpm, 2.5Kg



29mm, 1,010W, 0-2,800rpm, 3,3Kg





M 12SC









CC 14STA 355mm, Bar dia-65mm, Pipe dia 125mm, 2000W,

3900rpm, 14.1 Kg CE 16SA

In Steel 1.6mm Stainless 1.2mm, 400W, 4,700rpm, 1.7Kg

Double Insulation Dust Extracting

CC 14STD

3800rpm, 17.0Kg

355mm, Bar dia- 65mm,

Pipe dia 130mm, 2200W,

Orbit Action

Lock

Carry Case

079 - 2685 8008

011 - 4752 8944

Handle Type

CC 14STDU

3800rpm, 17.0Kg

355mm, Bar dia- 65mm,

Pipe dia 130mm, 2200W,

LOWHIGH

Reversible. Orbital Cutting

Cutting width 82mm,

17,000rpm, 2,5Kg

Max Cutting depth 580W,

P 20ST



M 12SA2

Constant speed



control, Collet chuck 12mm,

1,700W, 22,000rpm, 6,2Kg



Equipped with pushing button for

easy bit change, Collet chuck 12mm,

900W, 25.000rpm, 3.3Kg





CV 350V

AUTO Mode 6,000-20,000rpm/15,000-20,000, 1.5Kg

350W, Oscillation Frequency Standard mode /







200V-240V, 2, 000W, LCD Display with temp. Buttons, 5 Stage switch: 50-650°C, in increments of 10°C, 0.79Kg



6.67L/Min, Hose length 10m, 12.4Kg

Induction motor, 1.5hp, 24L, 8bar, 28Kg

B 16RM Laser guide, Chuck 16mm, 12 Stage speed:

0.57Kg

RH 600T

200V-240V, 2,000W,

2 Heat settings: 250/500°C & 450-600°C,



Hose length 10m, 8.3Kg

2,000W, Max, Pressure

Registered & Head Office: Hikoki Power Tools India Pvt. Ltd. Plot No.9A, 1st Phase, Peenya Industrial Area, Bengaluru 560 058. India, Tel: 080 - 4117 0777 / 78 / 2839 6198 Fax: 080 - 4117 1222 Email: ho.mktg@hikoki-powertools.in Website: www.hikoki-powert (Formerly known as **Hitachi Koki India Private Limited**)

HITACHI
HITACHI POWER TOOLS

HIGH PERFORMANCE POWER TOOLS

POWER TOOLS

2020 - 2021

HITACHI POWER TOOLS

HiKOKI

UNLEASH the NEXT

Customer Support No. - 18005725726

Eco-Products **BRANCHES:** AHMEDARAD

BANGALORE 080 - 4117 0777 **HYDERABAD** 040 - 4013 8207 022 - 2775 8814 MUMBAI KOLKATA 033 - 2479 7542 BHUBANESHWAR 91- 98302 00254 COCHIN 95677 61040 **JAIPUR** 88240 99593 LUCKNOW 90267 53265 LUDHIANA 85910 91138 PUNE 97027 86342 044 - 2432 8681 / 2435 0111 CHENNA

For any Customer Support / Service **Toll Free Number**

GUWAHATI 98360 92333 **HEAD QUARTERS:**

DELHI

Shinagawa Intercity Tower A, 20th floor, 15-1, Konan 2-chrome, Minato-ku, Tokyo 108-6020, Japan. Tel: +81-3-5783-0601 Fax: +81-3-5783-0709



Closed on Saturdays / Sundays

and Public holidays.

250-3.100rpm, 750W, 75Kg

1,400W, Max, Pressure 100bar, Max. Water discharge:

5.5L/Min, Hose length 5m, 5.4Kg

AW 130 1,600W, Max, Pressure 130bar, Max. Water discharge: 6L/Min,



AW 150 150bar, Max. Water discharge: 1